



elcometer 2210 Zahn Viscosity Cups

Can be used in accordance with:

ASTM D1084
ASTM D4212
ASTM D3794



Easy-to-use stainless steel apparatus, for quick viscosity measurement of products on site or during production. The cup is first dipped into the product to be measured, then empties through the orifice.

The measured kinematic viscosity is generally expressed in seconds (s) flow time, which can be converted to centistokes (cSt).

Five different orifices for measurements between 5 and 1840cSt are available.

Technical Specifications

Model	Cup Number	Range Centistokes (cSt) *	Part Number
Elcometer 2210/1	1	May-56	K0002210M001
Elcometer 2210/2	2	21-231	K0002210M002
Elcometer 2210/3	3	146-848	K0002210M003
Elcometer 2210/4	4	222-1110	K0002210M004
Elcometer 2210/5	5	460-1840	K0002210M005
Accessories	2400 Viscosity Disk Conversion		KT002400N003
	Stopwatches		See Digital Stopwatch
	Viscosity Standard Oils for Calibration		See Viscosity Standard Oils

Elcometer provide a viscosity recalibration service using state of the art, climate controlled facilities, for information please contact BAMR

**for information only*



BAMR (Pty) Ltd, PO Box 23973, Claremont, 7735, South Africa
 Ph : 27 (0)21 683 2100, Fax : 27 (0)21 674 1485
 Email : sales@bamr.co.za, Web : www.bamr.co.za