# Portable Pen Type Vibration Tester TV200 / TV260



#### **Features**

- Prompt testing of vibration on the workshop machines.
- For quick checking of unbalance misalignment, bearings and gears
- Guard against mechanical malfunction
- Holding tested value for 40 seconds
- Automatic switch off after 40 seconds

## **Specifications**

Model TV200
Parameter RMS of Vibration Velocity (mm/s)

Testing Range Velocity:

0.01 mm/s - 199.9 mm/s (RMS)

Frequency Range Velocity: 10Hz - 1kHz

Accuracy +/-5% +/-2 Display  $3^{1}/_{2}$  digits LCD

refresh Interval about 0.5 second 2 x button batteries (LR44 or SR44)

Battery Capacity Approx. 5 hours working continuosly Operating temperature: 0-40 °C

**Environment Relative** 

Power supply:

Humidity <85%

Dimensions: 150mm x 22mm x 18mm Weight: 55g (include 2 batteries)

### TV260

Acceleration, Velocity, Displacement Acceleration:

 $0.01 \text{ m/S}^2 - 199.9 \text{ m/S}^2 \text{ (peak)}$ 

Velocity:

0.01 mm/s - 199.9 mm/s (RMS)

Displacement:

0.001 mm - 199.9 mm (peak-peak)

Acceleration: 10Hz - 1kHz Velocity: 10Hz - 1kHz Displacement: 10Hz - 500Hz

+/-5% +/-2 3 <sup>1</sup>/<sub>2</sub> digits LCD

2 x button batteries (LR44 or SR44) Approx. 5 hours working continuosly

0-40 °C

<85%

150mm x 22mm x 18mm 55g (include 2 batteries)

## Standard delivery

- Main Unit
- Protective sheath
- Button Battery
- Certificate
- Instruction Manual
- Warranty Card